

Compact AC Fan

轴流风扇



Compact AC axial fan generate air flow in the direction of the axis of rotation, compact and slim body design suitable for applications requiring ventilation and cooling where the entire space inside the device.

紧凑型轴流风机通过叶轮产生平行于旋转轴方向的风量，其紧凑、集成式的外形设计特别适用于空间狭小的应用场景。

FEATURES:

- * Operating ambient temperature
Ball bearing: -20°C to +60°C
Sleeve bearing: 0°C to +50°C
- * Average working life 30000 hours
- * Lead wire or terminal for option
- * 运行环境温度
滚珠轴承: -20°C to +60°C
含油轴承: 0°C to +50°C
- * 平均使用寿命 30000 小时以上
- * 可选引线式或插片式

Model 型号	Frequency 频率	Voltage 电压	Bearing Type 轴承	Current 电流	Power 功率	Speed 转速	Air Flow 风量	Noise 噪音	Weight 重量
8025 - 80 x 80 x 25mm Square									
AF-8025-1S	50/60 Hz	110 V	Sleeve	0.13 / 0.12 A	13 / 12 W	2450 rpm	16 / 18 cfm	28 / 29 dB	230 g
AF-8025-1B	50/60 Hz	110 V	Ball	0.13 / 0.12 A	13 / 12 W	2450 rpm	16 / 18 cfm	28 / 29 dB	230 g
AF-8025-2S	50/60 Hz	220 V	Sleeve	0.08 / 0.07 A	13 / 12 W	2450 rpm	16 / 18 cfm	28 / 29 dB	230 g
AF-8025-2B	50/60 Hz	220 V	Ball	0.08 / 0.07 A	13 / 12 W	2450 rpm	16 / 18 cfm	28 / 29 dB	230 g
8038 - 80 x 80 x 38mm Square									
AF-8038-1S	50/60 Hz	110 V	Sleeve	0.15 / 0.13 A	14 / 13 W	2400 rpm	26 / 30 cfm	28 / 31 dB	240 g
AF-8038-1B	50/60 Hz	110 V	Ball	0.15 / 0.13 A	14 / 13 W	2400 rpm	26 / 30 cfm	28 / 31 dB	240 g
AF-8038-2S	50/60 Hz	220 V	Sleeve	0.08 / 0.07 A	14 / 13 W	2400 rpm	26 / 30 cfm	28 / 31 dB	240 g
AF-8038-2B	50/60 Hz	220 V	Ball	0.08 / 0.07 A	14 / 13 W	2400 rpm	26 / 30 cfm	28 / 31 dB	240 g
9225 - 92 x 92 x 25mm Square									
AF-9225-1S	50/60 Hz	110 V	Sleeve	0.14 / 0.12 A	13 / 12 W	2400 rpm	28 / 34 cfm	29 / 33 dB	270 g
AF-9225-1B	50/60 Hz	110 V	Ball	0.14 / 0.12 A	13 / 12 W	2400 rpm	28 / 34 cfm	29 / 33 dB	270 g
AF-9225-2S	50/60 Hz	220 V	Sleeve	0.08 / 0.07 A	13 / 12 W	2400 rpm	28 / 34 cfm	29 / 33 dB	270 g
AF-9225-2B	50/60 Hz	220 V	Ball	0.08 / 0.07 A	13 / 12 W	2400 rpm	28 / 34 cfm	29 / 33 dB	270 g
9238 - 92 x 92 x 38mm Square									
AF-9238-1S	50/60 Hz	110 V	Sleeve	0.15 / 0.13 A	15 / 13 W	2400 rpm	50 / 54 cfm	31 / 36 dB	360 g
AF-9238-1B	50/60 Hz	110 V	Ball	0.15 / 0.13 A	15 / 13 W	2400 rpm	50 / 54 cfm	31 / 36 dB	360 g
AF-9238-2S	50/60 Hz	220 V	Sleeve	0.08 / 0.07 A	15 / 13 W	2400 rpm	50 / 54 cfm	31 / 36 dB	360 g
AF-9238-2B	50/60 Hz	220 V	Ball	0.08 / 0.07 A	15 / 13 W	2400 rpm	50 / 54 cfm	31 / 36 dB	360 g
10826 - 92 x 92 x 26mm Square									
AF-10826-1S	50/60 Hz	110 V	Sleeve	0.16 / 0.14 A	16 / 15 W	2300 rpm	40 cfm	33 / 38 dB	330 g
AF-10826-1B	50/60 Hz	110 V	Ball	0.16 / 0.14 A	16 / 15 W	2300 rpm	40 cfm	33 / 38 dB	330 g
AF-10826-2S	50/60 Hz	220 V	Sleeve	0.08 / 0.07 A	16 / 15 W	2300 rpm	40 cfm	33 / 38 dB	330 g
AF-10826-2B	50/60 Hz	220 V	Ball	0.08 / 0.07 A	16 / 15 W	2300 rpm	40 cfm	33 / 38 dB	330 g
12025 - 120 x 120 x 25mm Square									
AF-12025-1S	50/60 Hz	110 V	Sleeve	0.15 / 0.14 A	16 / 15 W	2400 rpm	51 / 61 cfm	40 / 41 dB	380 g
AF-12025-1B	50/60 Hz	110 V	Ball	0.15 / 0.14 A	16 / 15 W	2400 rpm	51 / 61 cfm	40 / 41 dB	380 g
AF-12025-2S	50/60 Hz	220 V	Sleeve	0.08 / 0.07 A	16 / 15 W	2400 rpm	51 / 61 cfm	40 / 41 dB	380 g
AF-12025-2B	50/60 Hz	220 V	Ball	0.08 / 0.07 A	16 / 15 W	2400 rpm	51 / 61 cfm	40 / 41 dB	380 g
12038 - 120 x 120 x 38mm Square									
AF-12038-1S	50/60 Hz	110 V	Sleeve	0.24 / 0.23 A	26 / 23 W	2800 rpm	90 / 100 cfm	40 / 45 dB	500 g
AF-12038-1B	50/60 Hz	110 V	Ball	0.24 / 0.23 A	26 / 23 W	2800 rpm	90 / 100 cfm	40 / 45 dB	500 g
AF-12038-2S	50/60 Hz	220 V	Sleeve	0.14 / 0.13 A	26 / 23 W	2700 rpm	90 / 100 cfm	40 / 45 dB	500 g
AF-12038-2B	50/60 Hz	220 V	Ball	0.14 / 0.13 A	26 / 23 W	2700 rpm	90 / 100 cfm	40 / 45 dB	500 g
AF-12038-3S	50/60 Hz	380 V	Sleeve	0.07 / 0.06 A	26 / 23 W	2700 rpm	90 / 100 cfm	40 / 45 dB	500 g
AF-12038-3B	50/60 Hz	380 V	Ball	0.07 / 0.06 A	26 / 23 W	2700 rpm	90 / 100 cfm	40 / 45 dB	500 g