

Capacitor 电容器

CBB65-1 Motor Run Capacitor



FEATURES:

- * Explosion - proof design
- * Rated frequency: 50/60Hz
- * Quick connect terminals
- * Round metal housing
- * Capacitance tolerance: $\pm 5\%$
- * Working temp.: -40°C to $+70^{\circ}\text{C}$

Cap. μF	240V - 300V		350V - 400V		440V - 450V	
	Diam. mm	Height mm	Diam. mm	Height mm	Diam. mm	Height mm
2	40	55	40	55	40	55
3	40	55	40	55	40	55
4	40	55	40	55	40	55
5	40	55	40	55	40	55
7.5	40	55	40	65	40	65
10	40	55	40	55	40	65
12.5	40	55	40	65	40	75
15	40	55	40	65	40	75
17.5	40	65	40	75	40	75
20	40	75	45	75	50	65
25	40	75	45	85	50	75
30	45	75	50	75	50	85
35	45	75	50	75	50	85
40	45	85	50	85	50	100
45	45	100	50	100	50	110
50	45	100	50	100	50	110
55	50	90	50	110	50	125
60	50	100	50	125	50	125
65	50	110	50	125	55	110
70	50	125	55	110	55	125
80	50	125	55	125	60	125
100	55	125	60	125	60	140

CBB65-2 Motor Run Capacitor



FEATURES:

- * Explosion - proof design
- * Rated frequency: 50/60Hz
- * Quick connect terminals
- * Oval metal housing
- * Capacitance tolerance: $\pm 5\%$
- * Working temp.: -40°C to $+70^{\circ}\text{C}$

Cap. μF	350V - 400V			440V - 450V		
	Depth. mm	Width mm	Height mm	Depth. mm	Width mm	Height mm
5	31.5	51.5	55	31.5	51.5	55
10	31.5	51.5	55	31.5	51.5	65
15	31.5	51.5	65	31.5	51.5	75
20	31.5	51.5	75	31.5	51.5	85
25	45	71	55	45	71	65
30	45	71	65	45	71	75
35	45	71	75	45	71	85
40	45	71	85	45	71	90
45	45	71	90	45	71	100
50	45	71	90	45	71	100
60	45	71	100	45	71	110
70	45	71	110	45	71	125
80	45	71	110	48	90	100
100	45	71	125	48	90	125

CBB65-A Motor Run Capacitor



FEATURES:

- * Explosion - proof design
- * Rated frequency: 50/60Hz
- * Quick connect terminals
- * Round metal housing
- * Capacitance tolerance: $\pm 5\%$
- * Working temp.: -40°C to $+70^{\circ}\text{C}$

Cap. μF	370V		440V	
	Diam. mm	Height mm	Diam. mm	Height mm
15+1.5	50	65	50	75
20+1.5	50	75	50	85
25+3	50	75	50	85
30+5	50	85	50	95
35+5	50	95	50	105
40+5	50	105	50	120
45+5	50	105	50	120
45+7.5	50	120	50	125
50+5	50	120	50	125
50+6	50	120	50	125
50+7.5	50	120	50	125
55+7.5	50	125	55	125
60+7.5	50	125	55	125
65+7.5	55	125	60	120
70+7.5	55	125	60	125
80+10	60	125	60	135

CBB65-B Motor Run Capacitor



FEATURES:

- * Explosion - proof design
- * Rated frequency: 50/60Hz
- * Quick connect terminals
- * Oval metal housing
- * Capacitance tolerance: $\pm 5\%$
- * Working temp.: -40°C to $+70^{\circ}\text{C}$

Cap. μF	370V			440V		
	Depth. mm	Width mm	Height mm	Depth. mm	Width mm	Height mm
20+1.5	45	71	65	45	71	65
25+1.5	45	71	65	45	71	75
30+3	45	71	75	45	71	85
35+5	45	71	85	45	71	90
40+5	45	71	85	45	71	100
45+5	45	71	90	45	71	100
45+7.5	45	71	90	45	71	110
50+5	45	71	100	45	71	120
50+7.5	45	71	110	45	71	125
60+5	45	71	120	45	71	125
60+7.5	45	71	120	48	90	100
65+7.5	48	90	100	48	90	100
70+7.5	48	90	100	48	90	110
80+10	48	90	110	48	90	125

Capacitor 电容器

CBB61 Capacitor



FEATURES:

- * Self-extinguishing plastic case composition, filled with epoxy resin, spade terminals
- * Self-recovery after overheating
- * Small sizes fit most mini-splits and portable units, 50/60Hz AC motors, air conditioner and heat pumps, etc.
- * Capacitance tolerance: $\pm 5\%$
- * Working temp.: -40°C to $+70^{\circ}\text{C}$

Cap. μF	250V Dimension mm	370V Dimension mm	450V Dimension mm
1	36 x 12 x 23	36 x 12 x 23	36 x 12 x 23
1.2	36 x 12 x 23	36 x 12 x 23	36 x 12 x 23
1.5	36 x 12 x 23	36 x 12 x 23	36 x 12 x 23
2	36 x 12 x 23	37 x 15 x 26	37 x 15 x 26
2.5	37 x 15 x 26	37 x 15 x 26	38 x 18 x 28
3	37 x 15 x 26	38 x 18 x 28	38 x 18 x 28
3.5	37 x 15 x 26	38 x 18 x 28	47 x 18 x 29
4	38 x 18 x 28	38 x 18 x 28	47 x 18 x 29
5	38 x 18 x 28	47 x 18 x 29	47 x 18 x 34
6	47 x 18 x 29	47 x 18 x 34	47 x 22 x 34
7	47 x 18 x 29	47 x 22 x 34	48 x 26 x 38
8	57 x 18 x 32	47 x 22 x 34	48 x 26 x 38
10	57 x 18 x 32	57 x 21 x 35	58 x 23 x 37
12	57 x 21 x 35	58 x 23 x 37	58 x 28 x 40
14	57 x 21 x 35	58 x 23 x 37	58 x 28 x 40
15	57 x 21 x 35	58 x 28 x 40	58 x 28 x 40
16	58 x 23 x 37	58 x 28 x 40	58 x 30 x 48
18	58 x 23 x 37	58 x 28 x 40	58 x 30 x 48
20	58 x 28 x 40	58 x 30 x 48	58 x 40 x 45

CBB60 Capacitor



Using in running single phase asynchronous motors, applications at 50/60Hz. With self-extinguishing plastic case filled with resin allows for superior reliability and a high vibration strength, has long life-span and excellent self-healing feature.

Cap. μF	250V		370V		450V	
	Diam. mm	Height mm	Diam. mm	Height mm	Diam. mm	Height mm
2	25	50	25	50	25	50
3	25	50	25	50	30	50
4	25	50	30	50	30	50
5	25	50	30	50	30	60
7.5	30	50	30	60	32	60
10	30	60	35	60	35	70
12.5	30	60	35	60	35	70
15	34	60	35	70	38	70
17.5	34	60	35	70	40	70
20	35	70	38	70	40	70
25	42	70	42	80	45	70
30	42	70	42	80	45	90
35	42	80	42	90	45	90
40	42	80	42	90	45	90
45	42	90	45	90	50	90
50	45	90	45	90	50	90
55	45	90	50	90	50	100
60	50	90	50	100	50	120
65	50	100	50	100	50	120
70	50	100	50	120	55	120
75	50	100	50	120	55	120
80	50	120	55	120	60	120
90	50	120	55	120	60	120
100	55	120	60	120	60	120

CD60 Motor Start Capacitor



The CD60 series motor start capacitors are designed for the use of AC motor starting and other intermittent applications.

Cap. μF	110V - 125V		200V - 220V		300V - 330V	
	Diam. mm	Height mm	Diam. mm	Height mm	Diam. mm	Height mm
43 - 53	36.5	70	36.5	70	46	86
64 - 72	36.5	70	36.5	86	46	86
72 - 88	36.5	70	36.5	86	46	86
88 - 108	36.5	70	46	86	46	86
108 - 130	36.5	70	46	86	46	86
124 - 149	36.5	70	46	86	46	86
130 - 156	36.5	70	46	86	46	111
161 - 193	36.5	70	46	86	46	111
189 - 227	36.5	70	46	86	52	111
216 - 259	36.5	70	46	86	52	111
233 - 280	36.5	70	46	86	52	111
243 - 292	36.5	70	46	86	52	111
270 - 324	36.5	70	46	111	52	111
324 - 388	36.5	86	46	111	52	111
340 - 408	36.5	86	46	111	52	111
378 - 454	36.5	86	46	111	52	111
404 - 480	36.5	86	46	111	52	111
430 - 516	36.5	86	46	111	52	111
540 - 648	46	86	52	111	65	111
590 - 708	46	86	52	111	65	111
708 - 850	46	111	52	111	65	111
829 - 915	46	111	52	111	65	111
1000 - 1200	52	111	65	111	65	111

Hard Start Kit



FEATURES:

- * For all PSC A/C units from 4000 thru 12000 BTU's (1/2 HP thru 10 HP)
- * Can be used on 115 - 288 VAC
- * Easy 2-wire installation

Model	Operating Voltage	Application	Torque Increase
SPP5	115 - 288 VAC	1/2 to 10 HP	300 %
SPP6	115 - 288 VAC	1/2 to 10 HP	500 %
SPP8	115 - 288 VAC	1/2 to 10 HP	600 %